



EOS M 300 Series Digital Additive Manufacturing for the Industrial Production of High-Quality Metal Parts

- Reliable and repeatable quality
- Up to 10x higher productivity
- Easily integrated in production



EOS M 300 Series

Enables DMLS Quality with up to 10x Higher Productivity

Designed for industrial applications, the EOS M 300 Series offers multiple configuration options combined with safety and security features enabling digital Additive Manufacturing. The platform offers the flexibility to choose the degree of automation that best suits your needs for an optimized workflow as well as the option to easily ramp-up as demand increases.

Exposure Module

Number of Lasers



Laser Power



Laser Focus




Up to four precise lasers expose in a 300 x 300 mm square with each laser covering the entire area.

Dispenser Modules



Flexible Dispenser
Offers fast and easy material change.



Integrated Dispenser
Automated feeding enabling closed loop powder supply.


Clamping Modules




Select from 3 different models for easy integration to the post-processing equipment in your production facility.

Material & Process


EOS NickelAlloy



EOS MaragingSteel



EOS Titanium



EOS Aluminium



EOS StainlessSteel




EOS Materials are designed specifically for DMLS and are quality controlled.

EOS Processes are validated ensuring consistent and repeatable part quality.



EOSTATE Monitoring Suite

- 
EOSTATE
 Quality Reports
- 
EOSTATE
 MeltPool
- 
EOSTATE
 Exposure OT
- 
EOSTATE
 PowderBed

The automated and intelligent multi-monitoring suite for quality control and process development. EOSTATE enables insights in all production and quality relevant data - in real time.

Part Handling



EOS Transfer Station M

IPM M Setup Station M

EOS Transfer Station M
Fast switch-over of the exchangeable frame.

IPM M Setup Station M
Comfortable gas-tight unpacking from two sides and under inert gas.

Unpack Module*
Automated unpacking and easy integration in the IPM M Setup Station M.

Powder Handling



IPCM M extra
Manual and flexible powder handling.

IPCM M pro
Semi-automated powder handling.

IPM M Powder Station L
Automatic closed loop powder handling.

Software



EOSYSTEM
Intuitive industry proven machine software optimized for production.



EOSPRINT
Intuitive and easy job preparation and process development.



EOSCONNECT
Easy software integration into a production facility.

EOS M 300-4


Technical Data

Building volume	300 x 300 x 400 mm (11.8 x 11.8 x 15.8 in)
Laser type	Yb-fiber laser; 4 x 400 W
Precision optics	4 F-theta-lenses; 4 high-speed scanners
Scanning speed	up to 7.0 m/s (23 ft/s)
Focus diameter	approx. 100 µm (0.004 in)
Power supply	3 x 80 A
Power consumption	max. 36 kW / typical 26 kW
Inert gas supply	7 000 hPa; 15 m ³ /h (102 psi; 530 ft ³ /h)


Dimensions & Weight

EOS M 300-4 with Flex Dispenser

Height: 2340 mm / Weight: ca. 6600 kg




EOS M 300-4 with Integrated Dispenser*




EOS Transfer Station M

Height: 1300 mm / Weight: ca. 1000 kg



IPM M Setup Station M*

Height: 2000 mm / Weight: ca. 1400 kg



System

Workspace

Interface

*in development

Headquarters

EOS GmbH
Electro Optical Systems
Robert-Stirling-Ring 1
D-82152 Krailling/Munich
Germany
Phone +49 89 893 36-0
info@eos.info

www.eos.info

in EOS

Twitter EOSGmbH

Instagram EOS.global

YouTube EOSGmbH

#ShapingFuture

#ResponsibleManufacturing

Further Offices

EOS France
Phone +33 437 497 676

EOS Greater China
Phone +86 21 602 307 00

EOS India
Phone +91 443 964 8000

EOS Italy
Phone +39 023 340 1659

EOS Japan
Phone +81 45 670 0250

EOS Korea
Phone +82 2 6330 5800

EOS Nordic & Baltic
Phone +46 31 760 4640

EOS of North America
Phone +1 877 388 7916

EOS Singapore
Phone +65 6430 0463

EOS UK
Phone +44 1926 675 110

