




FORMIGA P 110 *Velocis*  
High Performance and Outstanding  
Part Quality at the Smallest Footprint

# FORMIGA P 110 *Velocis*

## The Benchmark in Plastic 3D Printing With a Batch Volume of 16.5 Liters

The most successful industrial 3D printer is now up to 20 % more productive thanks to new software and hardware features. Maintaining high reliability and FORMIGA quality, which set the standard in the market, the cost is more attractive than ever.



- Innovations in temperature management and software control accelerate heating and recoating process significantly increasing productivity.
- The running costs are only consumed material and power. No hidden costs. No agents.
- The precise laser spot with a small focus diameter enables wall thicknesses of less than a half millimeter. The system reliably produces small, delicate parts with the highest surface quality.
- The system ensures reproducible part properties throughout the entire build volume: for every build job and for every machine.
- Parts are fully functional right after unpacking and depowdering. No further post-processing needed.
- The spot pyrometer enables continuous and accurate temperature control.
- With 9 commercial polymer materials and 10 combinations of materials/layer thicknesses, EOS is a benchmark in terms of material variety. The EOS ParameterEditor allows customized exposure parameters to be defined based on a proven baseline.
- The system is user-friendly, requires low-maintenance and a minimum of accessories.

### Headquarters

EOS GmbH  
Electro Optical Systems  
Robert-Stirling-Ring 1  
D-82152 Krailling/Munich  
Germany  
Phone +49 89 893 36-0  
info@eos.info

www.eos.info

EOS  
 EOS3DPrinting  
 EOS3DPrinting  
#responsiblemanufacturing  
#futureisadditive

### Further Offices

EOS France  
Phone +33 437 497 676

EOS Greater China  
Phone +86 21 602 307 00

EOS India  
Phone +91 443 964 8000

EOS Italy  
Phone +39 023 340 1659

EOS Japan  
Phone +81 45 670 0250

EOS Korea  
Phone +82 2 6330 5800

EOS Nordic & Baltic  
Phone +46 31 760 4640

EOS North America  
Phone +1 877 388 7916

EOS Singapore  
Phone +65 6430 0463

EOS UK  
Phone +44 1926 675 110

### Technical Data FORMIGA P 110 *Velocis*

Building volume	200 x 250 x 330 mm (7.9 x 9.8 x 13 in)
Laser type	CO <sub>2</sub> ; 30 W
Building rate	up to 1.2 l/h
Layer thickness (depending on material)	0.06 – 0.10 – 0.12 mm (0.0024 – 0.0039 – 0.0047 in)
Precision optics	F-theta lens, high-speed scanner
Scan speed during build process	up to 5 m/s (16.4 ft/s)
Power supply	16 A
Power consumption	typical 3 kW, maximum 5 kW
Dimensions (W x D x H)	1320 x 1067 x 2204 mm (51.97 x 42.01 x 86.77 in)
Recommended installation space	min. 3.2 x 3.5 x 3.0 m (126 x 138 x 118 in)
Weight	approx. 600 kg (1323 lb)

### Software

EOSPRINT 2, EOSCONNECT



### Materials

PA 1101, PA 1101 ClimateNeutral, PA 1102 black, PA 2200®, PA 2200® CarbonReduced, PA 2201, PA 3200 GF, Alumide®, EOS TPU 1301

### Optional Accessories

Mixing station, unpacking and sieving station, blasting cabinet

